



Compressor  
Voltage Code : FZ

# AE4460E-FZ1B

High Temp. Commercial (HP)

220 - 240V 1~ 50 Hz

## R22

Conditions	Frequency	Nominal Cooling Capacity		Sound Power ISO3745 / ISO 3743-1
		Watts	BTU/h	
EN12900_HP / R22	50 Hz	1421	4846	

**Current**

**Refrigerating connection for OD**

\* EN12900\_HP : T°Cond. 50.0°C / T°Evap. 5.0°C / T°Return gas temp.. 20.0°C  
T°Subcooling. 0.0K

Note : Tecumseh reserves the right to change information contained in this document without notification.



**Tecumseh**

<b>AE4460E-FZ1B</b>	<b>Tension FZ : 220 - 240V 1~ 50 Hz</b>
---------------------	---

Les performances sont données dans les <b>conditions EN12900_HP :</b> Condition Dew	Gaz aspirés : 20.0 °C Sous refroidissement : 0.0 K
The performance data are in <b>EN12900_HP conditions :</b> Dew Condition	Return gas : 20.0 °C Subcooling : 0.0 K

**50 Hz R22**

**N°3104**

4   T condensation	5   T évaporation	(°C)	-20	-15	-10	-5	0	5	10	15
<b>40</b>	1   P frigorifique	(Watt)	563	688	860	1073	1323	1604	1912	2242
	2   P absorbée	(W)	379	414	448	480	509	534	554	568
	3   I absorbée	(A)	2.68	2.79	2.91	3.03	3.14	3.24	3.33	3.38
<b>50</b>	1   P frigorifique	(Watt)	458	588	755	952	1176	1421	1682	1953
	2   P absorbée	(W)	418	458	499	540	578	613	644	669
	3   I absorbée	(A)	2.82	2.95	3.10	3.26	3.41	3.56	3.69	3.81
<b>60</b>	1   P frigorifique	(Watt)		563	717	891	1081	1282	1488	1694
	2   P absorbée	(W)		501	552	603	654	702	747	787
	3   I absorbée	(A)		3.10	3.30	3.51	3.72	3.93	4.14	4.33

© 2021 Tecumseh Products Company  
All rights reserved

1 = cooling capacity 2 = power input 3 = current 4 = condensing temperature 5 = evaporating temperature

**Nota : Tecumseh se réserve le droit de modifier les informations contenues dans ce document sans préavis.**

**Note : Tecumseh reserves the right to change information contained in this document without notification.**